

Isopropyl Alcohol 異丙醇

Features 特性:

- 無色透明 colorless and transparent
- 溶解力強 miscible

Typical Application 一般應用:

- Injection:
 - 保護塗裝 Protective Coatings
 - 油墨 Inks
 - 清潔劑 Cleaning Compounds
 - 抗凍劑 Anti Freeze and De-icing Agent
 - 假漆稀釋劑 Lacquer Thinner Formulations
 - 硝化棉 Nitrocellulose

Typical Properties	Test Method	Unit	Value
一般性質	測試方法	單位	數值
Purity 純度	By GC	wt%	99.8 min
Water 水份	ASTM D 1364-90	wt%	0.15 max
Acidity 酸度	ASTM D 1613-91	wt%	0.001 max
Color 色度	ASTM D 1209-93	APHA	10 max
Specific Gravity 20/20°C 比重	ASTM D 268-90	-	0.785 ~ 0.787
Distillation Range 蒸餾範圍	ASTM D 1078-93	°C	1.0 (include 82.4°C)
Non-volatile Matter 不揮發物	ASTM D 1353-92	mg/100ml	5.0
Odor 味道測試	ASTM D 1296-93	-	Nonresidual
Solubility in Water 水溶解度	ASTM D 1722-90	-	passes test