



TECHNICAL DATA SHEET (TDS)

UD Carbon Fabric

N° SF2023-03
Date of previous issue:
Date of issue: 08/10/2023
Version: 1

Product/Prodotto/Produit:

UD CARBON FABRIC

Reference:

UD 600

Weight / Gramatura / Masse surfacique (g/m²)

600 +/- 5%

PRODUCT DESCRIPTION

Weave/Armatura/Armure

UNIDIRECTIONAL warp/ordito/chaine

Warp/Ordito/Chaine

3,75 x Aksaca® 24K A42

Weft/Trama/Trame

E glass Hotmelt

Edges/Giro/Bordure

E glass Hotmelt

Weight / Gramatura / Masse surfacique (+/-5%)

600g / m²

INPUT CARBON SPECIFICATION

Tensile strength	ISO10618	4200	Mpa
Tensile Modulus	ISO10618	240	Mpa
Strain	ISO10618	1.8	%
Weight (gx1000m)		1600	Tex

PACKING

Individual PE bag - sacco di PE per ogni rotolo - sac PE pour chaque rouleau

Inner core/Anima/Tube interne (diameter)		3'
Standard width/ Altezza/Largeur (-0/+2cm)*	cm	50
Standard Length/Lunghezza/longueur (+/-5%) ML	ML	50
Net weight /Peso netto /Poids net (+/-5%)	Kg	30